

◇ LC2500DC/LC2500DDC

发动机型号 Engine model	G200F/G200FD
发动机类型 Engine type	单缸、四冲程、强制风冷、顶置式气门 Single cylinder,4stroke, forced cooling ,OHV
输出功率 Power output	4.1kW/3600rpm
缸径×行程 Bore × Stroke	68mm×54mm (2.7"×2.1")
排量 Displacement	196cc
压缩比 Compression ratio	8.5 : 1
机油容量 Oil capacity	0.6L (0.16gal)
燃油箱容积 Fuel tank capacity	15L (4.0gal)
燃油消耗率 Fuel consumption	≤395g/kW.h
连续运行时间 Continuing time	12h
额定频率 Rated frequency	50 Hz/60 Hz
额定电压 Rated voltage	110V/115V/120V/220V/ 230V/240
调压系统 Voltage regulator system	自动电压调节 (Automatic Voltage Regulation)
额定输出功率 Rated output	2.0kW
最大功率 Max output	2.2kW
功率因数 Power factor	1.0
充电电压 Charging voltage	12V(DC)
充电电流 Charging current	8.3A(DC)
起动系统 Starting system	手拉反冲启动/电启动 (Recoil start/Electric-start)
点火系统 Ignition system	晶体管无触点点火 Transistorized magneto ignition
噪声 Noise (≤7m)	≤75dB(A)
外形尺寸 (长×宽×高) Dimension	590×475×460 (23.2"×22.6"×18.1")
净重 Net weight	43Kg (94.8lb)

可选配置: device option

- ◇ 油箱、启动器颜色和种类 color and type of fuel tank, starter
- ◇ 电压表指针式或数字式 pointer or digital voltage meter
- ◇ 车轮组件 wheel assy.
- ◇ 自启动或遥控启动 self-start or remote start



◇ LC3800DC/LC3800DDC

发动机型号 Engine model	G240F/G240FD
发动机类型 Engine type	单缸、四冲程、强制风冷、顶置式气门 Single cylinder, 4stroke, forced cooling, OHV
输出功率 Power output	5.2kW/3600rpm
缸径×行程 Bore × Stroke	73mm×58mm (2.9"×2.3")
排量 Displacement	242cc
压缩比 Compression ratio	8.2 : 1
机油容量 Oil capacity	1.1L (0.29gal)
燃油箱容积 Fuel tank capacity	25L (6.6gal)
燃油消耗率 Fuel consumption	≤374g/kW.h
连续运行时间 Continuing time	13h
额定频率 Rated frequency	50 Hz/60 Hz
额定电压 Rated voltage	110V/115V/120V/220V/ 230V/240
调压系统 Voltage regulator system	自动电压调节 (Automatic Voltage Regulation)
额定输出功率 Rated output	2.8kW
最大功率 Max output	3.1kW
功率因数 Power factor	1.0
充电电压 Charging voltage	12V(DC)
充电电流 Charging current	8.3A(DC)
起动系统 Starting system	手拉反冲启动/电启动 (Recoil start/Electric-start)
点火系统 Ignition system	晶体管无触点点火 Transistorized magneto ignition
噪声 Noise (≤7m)	≤76dB(A)
外形尺寸 (长×宽×高) Dimension	680×540×545 (26.8"×21.3"×21.5")
净重 Net weight	68Kg (150lb)

可选配置: device option

- ◇ 油箱、启动器颜色和种类 color and type of fuel tank, starter
- ◇ 电压表指针式或数字式 pointer or digital voltage meter
- ◇ 车轮组件 wheel assy.
- ◇ 自启动或遥控启动 self-start or remote start



◇ LC6500DC/LC6500DDC

发动机型号 Engine model	G390F/G390FD
发动机类型 Engine type	单缸、四冲程、强制风冷、顶置式气门 Single cylinder, 4stroke, forced cooling ,OHV
输出功率 Power output	8.2kW/3600rpm
缸径×行程 Bore × Stroke	88mm×64mm (3.5"×2.5")
排量 Displacement	389cc
压缩比 Compression ratio	8.0 : 1
机油容量 Oil capacity	1.1L (0.29gal)
燃油箱容积 Fuel tank capacity	25L (6.6gal)
燃油消耗率 Fuel consumption	≤374g/kW.h
连续运行时间 Continuing time	9h
额定频率 Rated frequency	50 Hz/60 Hz
额定电压 Rated voltage	110V/115V/120V/220V/ 230V/240
调压系统 Voltage regulator system	自动电压调节 (Automatic Voltage Regulation)
额定输出功率 Rated output	5.0kW
最大功率 Max output	5.5kW
功率因数 Power factor	1.0
充电电压 Charging voltage	12V(DC)
充电电流 Charging current	8.3A(DC)
起动系统 Starting system	手拉反冲启动/电启动 (Recoil start/Electric-start)
点火系统 Ignition system	晶体管无触点点火 Transistorized magneto ignition
噪声 Noise (≤7m)	≤76dB(A)
外形尺寸 (长×宽×高) Dimension	680×540×545 (26.8"×21.3"×21.5")
净重 Net weight	79Kg (174.2lb)

可选配置: device option

- ◇ 油箱、启动器颜色和种类 color and type of fuel tank, starter
- ◇ 电压表指针式或数字式 pointer or digital voltage meter
- ◇ 车轮组件 wheel assy.
- ◇ 自启动或遥控启动 self-start or remote start

